



ITEM # 1229C



1229C CYLINDER LOCKING HANDLE

- Fully door-mounted to assure locking regardless of door sag.
- Complete with revolutionary high strength, low maintenance No. inside safety release system.
- Installs on either right or left opening door with no modification.
- Handle is furnished with screw hole plugs for tamper-resistance*.
- Freezer Kit available for low temp application. Low temperature grease with insulation cup.

1229 NON-LOCKING HANDLE

Non-locking handle only.

SPECIFICATIONS

PULL HANDLE

MATERIAL:
High pressure die-cast zinc

FINISH:
See table below

MOUNTING:
Drilled and countersunk for 1/4" (6.0mm) fillister head or No. 12 (5.0mm) self-tapping screws

INSIDE RELEASE

MATERIAL:
Metal hub and flange, stainless steel arm and bolt, nylon shaft, polypropylene strike

MOUNTING:
Holes drilled and countersunk for No. 10 (5.0 mm) flat head screws

SHAFT LENGTHS:
Standard lengths for door thickness from 3-1/2" to 4" (88.9 mm to 101.6mm). Please specify door thickness. Custom lengths available to specification. Minimum wall thickness 2-1/4" (57mm)

Model No.	Description	Finish	Qty/ Carton	Wgt/ Carton
11229C00024	Cylinder Locking with Inside Release	Brushed Chrome	6	15.5 lb. (7.1 kg)
11229C00025	Cylinder Locking with Inside Release	Polished Chrome	6	15.5 lb. (7.1 kg)
11229C00028	Cylinder Locking with Inside Release & Freezer Kit	Brushed Chrome	6	15.5 lb. (7.1 kg)
11229C00029	Cylinder Locking with Inside Release & Freezer Kit	Polished Chrome	6	15.5 lb. (7.1 kg)
11229000004	Non-locking Handle	Brushed Chrome	6	12.5 lb. (5.7 kg)
11229000005	Non-locking Handle	Polished Chrome	6	12.5 lb. (5.7 kg)
11229C0002865	Cylinder Locking Handle With 948 ISR 6.5" Max Wall Freezer	Brushed Chrome		
11229C0002965	Cylinder Locking Handle With 948 ISR 6.5" Max Wall Freezer	Brushed Chrome		
90948000006	Freezer Kit			

Cylinder locks may be keyed alike or differently; 5 Key changes available; please specify.

FREEZER KIT

*Kit consists of plastic cap to cover rod, gasket for handle flange and special instructions for low temperature installations. When used with the specified low-temp grease, seals the unit to prevent accumulation of moisture.



PUSH PANEL

90171CM000411	Cylinder Kit #411
90171CM000414	Cylinder Kit #414

